

APNIC 54

rIGF2022

APSIG 2022

SGNOG 9

The Path to Resolverless DNS


Geoff Huston AM

Chief Scientist, APNIC


#apnic54



DNS System Architecture



DNS System Architecture



Issues

- **Speed** – the DNS can be exceptionally slow, and the interaction with resolver caches makes resolution unpredictable
- **Filtering** – the DNS is a convenient control point for content management
- **MetaData** collection – the DNS is a real time window on user behaviour
 - This can be performed at the recursive resolver, or by a third party on the path between the stub resolver and the recursive resolver
- **Search** – NXDOMAIN rewriting into active search

[What is this page?](#)

SEARCH

Sorry! We could not find [www.thisdomainnamedoesnotexist.org](#)

It may be unavailable or may not exist. Try using the suggestions or related links below, or search again using our web search.

No results

search results powered by **YAHOO!**

Searches related to: [www.thisdomainnamedoesnotexist.org](#)

[Home Network](#) [Networking](#) [Network Marketing](#) [Virtual Private Network](#)
[Network Security](#) [Network Management](#) [Kazaa](#)
[Network](#) [Computer Networking](#) [Network Solution](#)


powered by Nominum

SEARCH


Background

- Browser vendors were simplifying the UI and combined the navigation and search input boxes to a single window
- This resulted in a significant level of cross leakage between DNS and Search
- Some DNS resolver operators saw an opportunity to gather revenue by re-directing NXDOMAIN to search
- Google responded quickly with a large scale open DNS service that provided absolute integrity of responses, and supported DNSSEC validation to back this up
- Google's DNS service rapidly gathered momentum, particularly in the enterprise sector

DNS System Architecture



Use of Resolvers in the Internet



70% of users direct their DNS queries to the ISP-operated recursive resolvers

23% of users direct their DNS queries to Google's public DNS service

19% of users direct their DNS queries in in-country DNS

<https://stats.labs.apnic.net/rvrs>

But...

- DNS queries use unencrypted UDP by default
 - Which itself is a huge issue
- Combining this with a transit across the public Internet between the stub and open recursive resolver exposes further issues:
 - The potential for third party monitoring, interception and substitution
 - Loss of locational accuracy if the DNS is used to perform content steering for CDNs

DNS Privacy

The response to the issues of DNS over UDP has been the development of DNS stub-to-recursive connections over encrypted transport sessions

- **DNS over TLS** (DoT) uses DNS over TCP over a persistent TLS session
- **DNS over QUIC** (DoQ) uses DNS over an encrypted QUIC transport session over UDP
- **DNS over HTTPS** (DoH) uses DNS over HTTP/3 (over QUIC) where supported, and DNS over HTTP/2 (over TLS) otherwise

DoT/DoQ/DoH properties

- The stub resolver can authenticate the recursive resolver server identity
 - Which mitigates various forms of session interception
- Session encryption
 - Which mitigates various forms of payload tampering
- No Head of Line Blocking (in DNS over HTTPS/3, and DoQ)
- No UDP fragmentation and TCP failover issues
- Long-held stub/recursive sessions and TCPFO can amortise the encryption and session overheads over many queries
 - Which means it's not much different to UDP in terms of per query overheads in stub-to-recursive scenarios

Why DoH in particular?

- DoH is simply DNS queries and responses packaged with an HTTP header, so why bother? Why not just use DoT or DoQ?

One view:

Problems with DoH, part 1


- It's a political project, not a technical one
 - Encrypting stub-to-RDNS but not subsequent flows adds no actual privacy
 - An eavesdropper can guess DNS answers based on what happens afterward
 - Guessing the questions once you know the answers is trivial data science
- To stay out of jail in an authoritarian regime, you need a VPN
 - And once you have a VPN, what value would DoH add?
- Also note, many names are resolvable locally but not remotely
 - Most companies have their own internal-only TLD's like .CORP or .FORD
- The web is not the whole Internet; browsers can launch helper apps
 - Helper apps will use the normal stub resolver, getting different DNS answers

Why DoH?

- Maybe its more than a political project:
 - Because DoH sits alongside all other HTTPS traffic on TCP port 443 (HTTP/2) and UDP port 443 (HTTP/3) and is harder for network level isolation of DNS traffic
 - Because generic HTTP caching controls can be used to enable or disable the use of HTTP caching
 - Because HTTP/2 and HTTP/3 includes support for reordering, parallelism, priority and header compression
 - Because applications need not use the local stub DNS resolver and can direct DoH queries to a recursive resolver of its own choice
 - **Because DoH is an emerging browser default these days for encrypted DNS**

Why DoH?

Cloudflare Open Recursive Resolver DNS Query Profile for World (XA)



Some 18% of queries seen by Cloudflare's 1.1.1.1 service are over DoH

DoT usage is just under 5%

Why DoH?

- Because HTTP/2 and HTTP/3 includes “Server Push”

"Server Push"?

- RFC 7540: Hypertext Transfer Protocol Version 2 (HTTP/2)

8.2. Server Push

HTTP/2 allows a server to pre-emptively send (or "push") responses (along with corresponding "promised" requests) to a client in association with a previous client-initiated request. This can be useful when the server knows the client will need to have those responses available in order to fully process the response to the original request.

But in DoH this means...

- RFC 7540: Hypertext Transfer Protocol Version 2 (HTTP/2)

8.2. Server Push

HTTP/2 allows a server to pre-emptively send (or "push" responses (along with corresponding "promised" requests) to a client in association with a previous client-initiated request. This can be useful when the server knows the client will need to have those responses available in order to fully process the response to the original request.

DNS

DNS

DNS

What about HTTP/3?

- Yes – **draft-ietf-quick-http** supports server push

4.4. Server Push

Server push is an interaction mode that permits a server to push a request-response exchange to a client in anticipation of the client making the indicated request. This trades off network usage against a potential latency gain. HTTP/3 server push is similar to what is described in Section 8.2 of [HTTP2], but uses different mechanisms.

Each server push is assigned a unique Push ID by the server. The Push ID is used to refer to the push in various contexts throughout the lifetime of the HTTP/3 connection.

Which means...

- When a server sends a response to an HTTP request it can also push unrequested DNS responses
- This allows the user application to use these DNS resolution outcomes immediately and bypass DNS resolution delays
 - **It's faster**
- The user is not making these resolution queries, and is not generating meta data within the DNS
 - **It has some important privacy benefits for users**

For Example:

Google search results for "DNS over HTTPS". The search bar shows "DNS over HTTPS" with a search icon. Below the search bar are filters for "All", "News", "Videos", "Books", "Images", and "More". The results show approximately 124,000,000 results in 0.53 seconds. Several search results are highlighted with arrows pointing to them from the right side of the image:

- <https://developers.cloudflare.com/encryption/dns-over-https/>
DNS over HTTPS - Cloudflare 1.1.1.1 docs
3 days ago — With DNS over HTTPS (DoH), DNS queries and responses are encrypted and sent via the HTTP or HTTPS protocols. DoH ensures that attackers ...
Configure DoH on your browser · Connect to 1.1.1.1 using DoH... · Using JSON
- https://en.wikipedia.org/wiki/DNS_over_HTTPS
DNS over HTTPS - Wikipedia
DNS over HTTPS (DoH) is a protocol for performing remote Domain Name System (DNS) resolution via the HTTPS protocol. A goal of the method is to increase ...
Technical details · Oblivious DNS-over-HTTPS · Software support
- People also ask**
 - Should I use DNS over HTTPS?
 - What is DNS over HTTPS setting?
 - Is enable DNS over HTTPS safe?
 - Why is DNS over HTTPS controversial?
- [https://www.techtarget.com/searchsecurity/definition/What-is-DNS-over-HTTPS-\(DoH\)-/](https://www.techtarget.com/searchsecurity/definition/What-is-DNS-over-HTTPS-(DoH)-/)
What is DNS over HTTPS (DoH)? - TechTarget
DNS over HTTPS (DoH) is a relatively new protocol that encrypts domain name system traffic by passing DNS queries through a Hypertext Transfer Protocol ...
How DoH Works · Benefits Of DoH · Criticism And Controversy
- <https://support.mozilla.org/en-US/firefox-dns-over-https/>
Firefox DNS-over-HTTPS - Mozilla Support
Scroll down to Network Settings and click the Settings... button. Click the Use Provider dropdown under Enable DNS over HTTPS to select a provider in the list.
About Dns-Over-Https · Risks · Excluding Specific Domains
- <https://heimdalsecurity.com/blog/dns-over-https-doh/>
DNS over HTTPS (DoH): Definition, Implementation, Benefits ...
Jul 13, 2021 — DNS over HTTPS (abbreviated as DoH) is an internet security protocol that

Potential Server Push DNS objects

But ...

- How do you know that the server is pushing the “truth” when it provides these DNS answers?
- The secure transport means that tampering is challenging, but the user should still validate these responses (assuming that they are DNSSEC-signed in the DNS)
- Which would mean that the user still has to chase down the DNSSEC validation chain, and most of the the original speedup advantages are lost

But ...

Or maybe not...

- The server could also push the collection of DNSSEC validation responses to the client
- The server could also repackage these responses into a RFC 7901 EDNS0 Chain Response, attached to the original response
- That way the response and the reason why the response is authentic can be packaged into a single pushed DNS object

DNSSEC-Validated DNS data

DNSSEC validation provides the user with assurance that the data is:

- Authentic
 - Current
 - Complete (for each RRType)
- If that's the case then why does it matter how the stub learned the data?
 - It could be a DNS query / response transaction
 - It could be via a server push over DoH

DNSSEC validation is providing the assurance that the data is usable

What if the pushed DNS response is unsigned?

Er, um, er...

- It's probably best to discard it!
 - You have no idea how the server obtained the DNS data in the first place
 - You don't know how current the data is
 - You really don't know if the server is trying to deceive you
 - And you have no idea who you are implicitly trusting if you use the data

What can we say about Resolverless DNS?

- It gives HTTP-based applications and services far more control over the quality of the user experience
 - It allows the server to pre-provision the client with DNS data that is likely to be useful in the context of the application
 - It allows the client side application to perform rapid DNSSEC validation without relying on stub resolver capabilities and settings
 - It can replace UDP-based timers, query retries, fragmentation and TCP switching with server-to-client provision
 - It operates over a secured connection with an authenticated server
 - It does not leak metadata through DNS query streams

As long as the DNS data is DNSSEC-signed

What about unsigned DNS data?

Forget it!

- Resolverless DNS responses of unsigned DNS data just opens up more potential vulnerabilities with little in the way of reasonable mitigation

Where is this leading?

The changing economics of the Internet

- The shift to advertiser-funded content and service has sucked the revenue base from access and common infrastructure
- Internet infrastructure is a commodity-based activity which resists innovation
- The incentives to innovate lie in the application and service layers
- Infrastructure is under continued pressure to achieve further efficiencies and there is a consequent pressure to scale up and centralise

The DNS is caught up in this, and innovation in the DNS is extremely challenging to get adoption these days

Does Resolverless DNS have a chance?

Is there a role for Resolverless DNS?

Perhaps - but, to be trustable it requires DNSSEC - which is a tough assumption

- Few zones are DNSSEC-signed
 - Because DNSSEC signatures tend to create larger responses, which is a problem in DNS over UDP
 - Because pre-signing is infeasible for very large zones
 - Because signing on the fly can be fragile
- Few resolvers validate
 - Because of the time and resolution robustness issues

What about RFC 7901?

- What if a pushed DNS response was framed as if the client had set the EDNS0 CHAIN option with the root zone as the closest trust point?
- That way the client is provided with the DNS response and the chain of signatures that permit the client to perform local validation of the response in a single pushed DNS object
- And if the zone is unsigned - then no DNS response is pushed

Why is this interesting?

The DNS is:

- A massive time penalty
- A significant privacy leak
- A consistent source of failure

Resolverless DNS won't fix all the DNS all at once

- But it can hand a significant amount of control over application and service quality back to these HTTPS-based applications and services
- It can allow the end client to directly validate DNS information without blind trusting in a recursive resolver
- And it's a whole lot faster!
- And it hides the client from the DNS resolution infrastructure

And for those reasons it's a very interesting step in the possible evolution of the DNS

Why is this interesting?

We have spent a huge amount of effort over the last decade trying to make the Internet faster:

- We've been deploying CDNs to replicate content and services and bring them closer to users
- We've been deploying non-blocking transport protocols (such as QUIC) to exploit parallelism
- We've been tuning TCP and network behaviour to create more efficient and faster network transactions
- We've been packing more information in the DNS to make service startup faster (SVC and HTTPS records)
- And much of this innovation is happening at the application levels of the protocol stack where there is ample money and an impatient agenda, avoiding incurring any further dependencies on the lower layers of common infrastructure where there is neither money nor impatience!

Thanks!

APNIC

54

SINGAPORE

8 - 15 September 2022

#apnic54

APrIGF 2022

APSIG 2022

SGNOG 9